



Ceramic processing of tubular, multilayered oxygen transport membranes (Invited)

Bjørnetun Haugen, Astri; Ovtar, Simona; Gurauskis, J.; Kaiser, Andreas; Kiebach, Wolff-Ragnar; Hendriksen, Peter Vang

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Bjørnetun Haugen, A., Ovtar, S., Gurauskis, J., Kaiser, A., Kiebach, W-R., & Hendriksen, P. V. (2017). *Ceramic processing of tubular, multilayered oxygen transport membranes (Invited)*. Abstract from 41st International Conference and Expo on Advanced Ceramics and Composites , Florida, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Ceramic processing of tubular, multilayered oxygen transport membranes (Invited)

A. B. Haugen*¹; S. Ovtar¹; J. Gurauskis²; A. Kaiser¹; R. Kiebach¹; P. Hendriksen¹;

1. Technical University of Denmark, Denmark;

2. Aneam IVS, Denmark

Pure oxygen gas supplied by ceramic oxygen transport membranes (OTMs) can facilitate reduced CO₂ emissions through more efficient gasification or combustion processes and easier CO₂ capture and storage. For maximum oxygen flux and 100% selectivity, the active OTM layer should be thin and dense, and have a large and catalytically activated surface area. These requirements call for an asymmetric OTM design with a thin, dense OTM layer (~15 µm) sandwiched between two porous catalyst layers (~15 µm) and mechanically supported on a porous ceramic substrate (~1 mm). This talk pertains to our work at the Technical University of Denmark (DTU) related to processing such multilayered ceramic components with a tubular geometry, focusing on scalable process technologies. This includes thermoplastic extrusion to shape the porous, tubular support, deposition of thin dense and porous layers by dip coating, co-sintering of these layers, and infiltration of electrocatalysts. Material and processing considerations for two different combinations of materials in the multilayered components will be discussed, and performance of these components under laboratory testing and integrated in pilot-scale biomass gasifiers will be presented.